

# FICUS F



*Ficus  
F 2000*

Trailed type, powered by Tractor PTO via a shielded shaft. Required tractor power is 60 HP. Suitable for spraying orchard fields and gardens.

#### General Characteristics

- Easily adjustable and user friendly,
- High efficiency,
- Polyethylene tank,
- Turbo fan case is made of ni-cr stainless steel or galvanized,
- Angle adjustable or high flowrate fan,
- Easily cleanable water filter,
- Optional auxiliary clean water tank,
- Homogeneous mixing of water and pesticide at hydraulic mixer,
- Pressure regulation,
- Quick filling of pesticide at 30 bar high pressure,
- Easily mountable on tractor drawbar by means of jack leg with wheel,
- Discharge beam length of spray can be adjusted at the nozzle,
- Level indicator on the tank,
- Fun hub and blades are made of hard plastic.



## Ficus F 2000

Type	FICUS F 1000	FICUS F 1600	FICUS F 2000
Pump (l/m)	C145	C145	C145
Control Panel	BY MATIC	BY MATIC	BY MATIC
Nozzle	Brass	Brass	Brass
Nr. Of Nozzle	8+8	8+8	8+8
Width (cm)	158	170	179
Length (cm)	376	400	428
Height (cm)	130	140	150
Fan Diameter (cm)	92	92	92
Working Width (m)	8-12	8-12	8-12
Required (HP)	60	60	60
Speed RPM	540	540	540
Air Flowrate (m3/h)	66000	66000	66000
Weight (kg)	516	550	576



Wheels, suitable for any field condition



C-145 pump with 145 lt/min flowrate.



Turbo control unit, compatible with high pressure pumps.



Jack Leg.



Easy cleanable Filter, resistant to high pressure.



Ficus Turbo Fan.



Pressure filter, with self-cleaning.



Angle adjustable nozzle.

TURBO